

United States Patent [19]

Jacobson et al.

6,130,773 **Patent Number:** [11]

Date of Patent: *Oct. 10, 2000 [45]

[54]	NONEMISSIVE DISPLAYS AND
	PIEZOELECTRIC POWER SUPPLIES
	THEREFOR

[75] Inventors: Joseph M. Jacobson; Barrett

Comiskey, both of Cambridge, Mass.

Assignee: Massachusetts Institute of

Technology, Cambridge, Mass.

This patent is subject to a terminal dis-[*] Notice:

claimer.

[21] Appl. No.: 09/189,254

[22] Filed: Nov. 10, 1998

Related U.S. Application Data

Continuation of application No. 08/738,260, Oct. 25, 1996, Pat. No. 5,930,026.

Int. Cl.⁷ G02B 26/00; G09G 3/34; G09F 1/00

U.S. Cl. **359/296**; 345/107; 40/124.02;

40/124.09 40/124.01, 124.02, 124.09, 124.11, 124.12;

36/136, 137

[56] **References Cited**

U.S. PATENT DOCUMENTS

2,800,457	7/1957	Green et al
3,036,388	5/1962	Tate
3,406,363	10/1968	Tate
3,460,248	8/1969	Tate 29/607
3,585,381	6/1971	Hedson et al
3,668,106	6/1972	Ota .
4,001,140	1/1977	Foris et al
4,088,395	5/1978	Giglia 350/357
4,093,534	6/1978	Carter et al
4,126,854	11/1978	Sheridon 340/373

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

0 186 710 A1 7/1986 European Pat. Off. .

(List continued on next page.)

OTHER PUBLICATIONS

J. Sankus "Electrophoretic Display Cell," Xerox Disclosure Journal, Abstract, vol. 4, No. 3, May/Jun. 1979.

Nuno A. Vaz et al., "Dual frequency addressing of polymer-dispensed liquid-crystal films," *Journal of Applied Physics*, vol. 65, No. 12, Jun., 1989, pp. 5043-5049.

Lawerence L. Lee, "Fabrication of Magnetic Particles Display," Proceedings of the S.I.D., vol. 18, Nos. 3&4, 1977, pp. 283-288.

N.K. Sheridon et al., "Gyricon—A Twisting Ball Display," Proceedings of the S.I.D., vol. 18, Nos. 3&4, 1977, pp. 289-293.

(List continued on next page.)

Primary Examiner—Georgia Epps Assistant Examiner—Evelyn A. Lester Attorney, Agent, or Firm—Cesari and McKenna, LLP

ABSTRACT [57]

An electrophoretic display has a substantially twodimensional arrangement of microcapsules each having therein an electrophoretic composition of a dielectric fluid and a suspension of particles that visually contrast with the dielectric liquid and also exhibit surface charges; a pair of electrodes, at least one of which is visually transparent, disposed on and covering opposite sides of the microcapsule arrangement; and a power source for creating a potential difference between the two electrodes, the potential difference causing the particles to migrate toward one of the electrodes. The display may be powered by one or more piezoelectric elements, which are also suitable for powering other types of nonemissive displays.

3 Claims, 5 Drawing Sheets

